



Kingfisher 1100 powercat example specification

Dimensions

✓	Hull length	11.25m
✓	Beam	4.25m
✓	Draft	0.5m
✓	Displacement	7000kg
✓	Fuel capacity	1000 (2 X 500litres)
✓	Fresh water	400 litres
✓	Holding tank	30 litre

Construction

- ✓ Marine grade 5083 aluminium
- ✓ Hull bottom: 6mm
- ✓ Hull sides: 5mm
- ✓ Superstructure: 3mm and 4mm
- ✓ Side sliding windows
- ✓ Two acrylic hatches to forward cabin.

Power

- ✓ Twin 315hp Yanmar with sternlegs (or equivalent)

Performance (Subject to loadings and sea conditions)

- ✓ Estimated Max speed: 40 knots
- ✓ Fast cruising speed: 20 to 24 knots

Electrical

- ✓ Anchor retrieval: Muir VRC 1250
- ✓ 12v electrical system throughout.
- ✓ 2 x start batteries to engine specifications
- ✓ House batteries: 2 banks deep cycle
- ✓ 4 x bilge pumps and float switches
- ✓ LED interior and navigation lights
- ✓ Fresh water pressure pump
- ✓ Washdown pump and hose
- ✓ Holding tank including pump out
- ✓ 3 DC sockets
- ✓ 2 x LED floodlights over cockpit
- ✓ 80l 12v freezer
- ✓ Fridge 130 litre 12V

Electronics

- ✓ VHF radio and aerial
- ✓ Stereo with 4 speakers and Ipod dock
- ✓ 9 inch GPS/Chartplotter

Finishes

- ✓ Saloon and forward cabins: wall carpeting
- ✓ Dash and mullions: paint
- ✓ Superstructure external: Painted to medium finish
- ✓ Hull: Painted to medium finish
- ✓ Cockpit floor: painted non-skid
- ✓ Internally carpeted

Layout -customised

- ✓ Central helm station with 2 x helm chairs
- ✓ Toilet/sink/shower aft of saloon - access from cockpit
- ✓ Port galley including fridge, sink and gas cooker
- ✓ Starboard "L" shaped seating with table
- ✓ 2 x fwd double berths
- ✓ 2 x single berths below saloon - access from fwd

Other

- ✓ Electric toilet
- ✓ Internal shower and toilet cubicle
- ✓ Shore power connection. Includes cables. Plugs, RCD, galvanic isolator, 30amp charger
- ✓ 1kw inverter plus microwave

Price (NZD including GST)

\$ 495,000.00